
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE XLD 20W50

Valvoline XLD 20W50 has been formulated from high quality paraffinic base oils having a good oxidation stability and high viscosity index. The incorporation of selected detergent, dispersant, anti-oxidant, anti-corrosive, anti-scuffing and anti-wear additives imparts the desired protective properties to the product for prolonged engine life.

Valvoline XLD 20W50 provides an ease of cold starting and higher viscosity at operating temperatures for better engine protection and reduced oil consumption. The molecules of this product cling to the metal surfaces even under severe driving conditions and high temperatures.

Valvoline XLD 20W50 is recommended for use in all makes of passenger cars.

Valvoline XLD 20W50 Advantage

- Superior engine protection & extended drain interval
- Engine protection during cold start and extreme heat.

Performance levels / Approvals

API SG/CD

Typical Characteristics

Appearance	Bright & Clear
Kinematic Viscosity, cSt @ 40°C	162
Kinematic Viscosity, cSt @ 100°C	18.0
Viscosity Index	122
TBN, mg KOH/g	5.3
Flash Point, COC, °C	210
Pour Point, °C, Max.	-24
CCS @ -15 °C, cP, Max.	9200

Available configurations: 24 x 1L Case, 4 x 4L Case, 4 x 5L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code