
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE ALL FLEET PLUS 30, 40 and 50

Valvoline All Fleet Plus grades are formulated from highly refined lube base stocks and carefully selected additive package comprising antioxidant, detergent/ dispersant, antiwear and a special oil soot thickening control agent.

Valvoline All Fleet Plus grades are recommended for use in high speed naturally aspirated and turbo/super charged diesel engines of all makes operating at low speed and high torque conditions prevalent in prolonged city stop-&-go, on-&-off highway driving conditions including service in hilly regions.

Performance levels / Approvals

API CF/SF

Typical Characteristics

SAE Grade	30	40	50
Kinematic Viscosity, cSt @ 40°C	103.60	143.6	187
Kinematic Viscosity, cSt @ 100°C	11.40	14.50	17.20
Viscosity Index	97	97	95
Flash Point, COC, °C, Min.	200	210	220

Available configurations: All Fleet Plus 30: 1 x 18L, 1 x 200L
All Fleet Plus 40: 24 X 1L Case, 4 x 5L Case, 1 x 18L, 1 x 200L
All Fleet Plus 50

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
1st March 2009

Authors Initials
SKM

Product code