
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE GEAR GARD SUPER 90 & 140

Valvoline Gear Gard Super 90 & 140 are thermally stable, superior sulphur-phosphorus extreme pressure gear lubricants with good anti-rust, anti-corrosion and anti-oxidant characteristics. These are multipurpose heavy duty type gear lubricants specially formulated to comply with the stringent service requirements of commercial fleet, mechanical transmission, axles & final drives operating under high speed, high load, high torque & high horse power conditions.

Valvoline Gear Gard Super 90 & 140 are recommended for use in conventional rear axles, limited slip rear axles & transmissions of Vehicles requiring EP gear oils to GL-5 performance level.

Performance levels / Approvals

API GL-5
MAN 342N, ZF TE –ML 05A & TE-ML 12E

Typical Characteristics

SAE Grade	90	140
Kinematic Viscosity, cSt @ 100°C	16.02	25.1
Viscosity Index	97	96
Pour Point, °C, Max.	-18	-9
Flash Point, COC, °C	210	210

Available configurations: 24 x 1L Case, 4 x 4L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code