
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE DEX III ATF

Valvoline Dex III ATF is formulated with a blend of high tech basestocks combined with advanced additive technology to meet the challenging demands of an automatic transmission environment. Valvoline Dex III ATF is designed to provide better heat resistance, cold flow capabilities and transmission shudder resistance than conventional automatic transmission fluids.

It is recommended for use in automatic transmission for GM & Ford passenger cars and light duty truck transmissions.

This product is also suitable for use in powershift transmissions, torque converters Hydrostatic transmissions and applications such as in air compressors, Hydraulic pumps and other types of service where an ATF is recommended.

Valvoline Dex III ATF Advantages:

- **Low Temperature Protection:** Flows easily at low temperatures.
- **Friction Modified:** Contains additives to protect automatic transmission hardware.
- **Cleaner Transmission:** Minimizes sludge and varnish deposits.
- **Compatibility:** Protects transmission seal materials.
- **Anti-Shudder:** Provides superior anti-shudder performance.

Performance levels / Approvals

DEXRON®-IIIH/M
Allison C-4
JASO 1-A

Typical Characteristics

Kinematic Viscosity, cSt @ 40°C	39.5
Kinematic Viscosity, cSt @ 100°C	7.5
Viscosity Index	160
Pour Point, °C, Max.	-48
Flash Point, COC, °C	200

Available configurations: 24 x 1L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code