
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE VR-1 RACING 15W40

Valvoline VR-1 Racing 15W40 is a race-proven lubricant formulated to provide high load carrying characteristics, minimum foaming and maximum resistance to thermal degradation. Exclusive chemistry reduces internal friction and enhances power output under extreme service conditions. **Valvoline VR-1 Racing 15W40** is recommended for engines burning gasoline and full or partial alcohol fuels in track and street service. **Valvoline VR-1 Racing 15W40** is for use in any car, light truck, van, or SUV where API "SM" is recommended .

Valvoline VR-1 Racing 15W40 is not recommended for use in wet clutches (use Valvoline 4-Stroke Motorcycle Oil).

The Valvoline VR-1 Racing 15W40 ADVANTAGE

- High performance and protection for today's engines that run at high RPM
- Enhanced anti-foam system helps protect the engine even during extreme stress
- Enhanced additive protects against high temperature deposits for a cleaner engine
- Friction modifiers help improve horsepower output

Performance levels / Approvals

API SM / SL / CF

Typical Characteristics

Kinematic Viscosity, cSt @ 40°C	114
Kinematic Viscosity, cSt @ 100°C	15.1
Viscosity Index	137
TBN, mg KOH/g	7.2
Flash Point, COC, °C	210
Pour Point, °C, Max.	-24
CCS @ -20 °C, cP, Max.	6700

Available configurations: 4 x 4L Case

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code